


FEATURES

- ◇ Low cost
- ◇ Diffused junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol,Isopropanol and similar solvents

MECHANICAL DATA

- ◇ Case: JEDEC DO-15, molded plastic
- ◇ Terminals: Axial lead , solderable per MIL- STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.014ounces, 0.39 grams
- ◇ Mounting position: Any

DO - 15

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase,half wave,50Hz,resistive or inductive load. For capacitive load,derate by 20%.

		BYV95A	BYV95B	BYV95C	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	200	400	600	V
Maximum RMS voltage	V_{RMS}	140	280	420	V
Maximum DC blocking voltage	V_{DC}	200	200	600	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^\circ\text{C}$	$I_{F(AV)}$	1.5			A
Peak forward surge current 10ms single half-sine-wave superimposed on rated load @ $T_j=125^\circ\text{C}$	I_{FSM}	50.0			A
Maximum instantaneous forward voltage @ 3.0A	V_F	1.6			V
Maximum reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	I_R	5.0 100.0			μA
Maximum reverse recovery time (Note1)	t_{rr}	250			ns
Typical junction capacitance (Note2)	C_J	18			pF
Typical thermal resistance (Note3)	$R_{\theta JA}$	45			$^\circ\text{C}/\text{W}$
Operating junction temperature range	T_j	-55 ---- + 150			$^\circ\text{C}$
Storage temperature range	T_{STG}	-55 ---- + 150			$^\circ\text{C}$

NOTE:1. Measured with $I_F=0.5\text{A}$, $I_R=1\text{A}$, $I_{rr}=0.25\text{A}$.

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.


3. Thermal resistance from junction to ambient.

FAST RECOVERY RECTIFIERS


BYV95A---BYV95C

VOLTAGE RANGE: 200 --- 600 V
CURRENT: 1.5 A

FIG.1 – REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




NOTES:
 1. RISE TIME = 7ns MAX. INPUT IMPEDANCE = 1MΩ. 22pF
 2. RISE TIME = 10ns MAX. SOURCE IMPEDANCE = 50Ω




SET TIME BASE FOR 50/100 ns /cm

FIG.2 – FORWARD DERATING CURVE




AVERAGE FORWARD CURRENT
AMPERES

FIG.3 – PEAK FORWARD SURGE CURRENT




NUMBER OF CYCLES AT 60 Hz

FIG.4–TYPICAL FORWARD CHARACTERISTIC



INSTANTANEOUS FORWARD CURRENT
AMPERES

FIG.5- TYPICAL JUNCTION CAPACITANCE



REVERSE VOLTAGE, VOLTS