

# LL4148


## FEATURES

- Silicon epitaxial planar diode
- Fast switching diodes
- 500mw power dissipation
- High temperature soldering guaranteed 250°C/10S at terminals

## MECHANICAL DATA

- Case: MINI MELF glass sealed envelope.
- Terminals : Solderable per MIL-STD-750, Method 2026
- Polarity : Color band denotes cathode end
- Mounting Position : Any
- Weight :0.002 ounce, 0.05 grams

### MINI MELF



Dimensions in inches and (millimeters)

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified.
- Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

	SYMBOLS	LL4148	UNITS
Maximum repetitive peak reverse voltage	$V_{RRM}$	100	VOLTS
Maximum RMS voltage	$V_{RMS}$	75	VOLTS
Maximum average forward rectified current 0.375" (9.5mm) lead length at $T_A=75^\circ\text{C}$	$I_{(AV)}$	150	mAmps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	500	mAmps
Maximum instantaneous forward voltage at 10mA	$V_F$	1.0	Volts
Maximum DC reverse current $T_A=25^\circ\text{C}$ $V_R=75\text{V}$ at rated DC blocking voltage $T_A=100^\circ\text{C}$ $V_R=20\text{V}$	$I_R$	5.0 50	$\mu\text{A}$
Maximum reverse recovery time (NOTE 1)	$t_{rr}$	4.0	ns
Typical junction capacitance (NOTE 2)	$C_J$	4.0	pF
Operating junction and storage temperature range	$T_J, T_{STG}$	-65 to +200	$^\circ\text{C}$

### NOTES:

1. Test condition:  $I_F=10\text{mA}$ ,  $I_R=10\text{mA}$ ,  $I_{rr}=1\text{mA}$ ,  $V_R=6\text{V}$ ,  $R_L=100\Omega$ .
2. Measured at 1.0 MHz and applied reverse voltage of 4.0 volts

### LL4148

FIG. 1-ADMISSIBLE POWER DISSIPATION VERSUS AMBIENT TEMPERATURE




FIG. 2-REVERSE CURRENT VERSUS CONTINUOUS REVERSE VOLTAGE (TYPICAL VALUES)




FIG. 3-FORWARD CHARACTERISTICS




FIG. 4-RELATIVE CAPACITANCE VERSUS REVERSE VOLTAGE





FIG. 5-MAXIMUM PERMISSIBLE NON-REPETITIVE PEAK FORWARD CURRENT AS A FUNCTION OF PULSE DURATION



Based on square wave currents.  $T_J = 25^\circ$  prior to surge.